



Nominal Dimensions in (mm)														Max Pad Depth	No. of Vanes	Air Gap	Weight Kg	Face Types Available	Comments	Part Numbers								
'A' Outside Dia.	'B' Thick-ness	Mounting Details				'C' (Eye) Ø.	'D' Inside Flange Ø.	'H' Mtg. Flange																				
		M* P.C.D.	No.	Fixing Type S/Bobbin - Standard CP2484, W/Bobbin - Heavy Duty CP4135 or CP7016	Ø.																							
300.0	24.0	189.0	8	Bolted	6.4	204.4	172.0	5.02	D47	48	9.0	4.5	G4	CP4348-106/7														
	25.4	190.0	8	Bolted	6.4	205.4	173.5	4.6	D46	24	15.5	3.3	G8	CP3047-398/9														
	25.4	196.2	12	Bolted	6.4	213.3	181.5	6.67	D42	48	9.0	4.6	P	CP4348-910/1														
	28.0	177.8	12	S/Bobbin		197.2	154.0	5.62	D50	48	14.0	5.0	RA	CP3580-1196/7														
	28.0	177.8	12	Bolted	6.4	203.2	164.0	5.6	D46	36	15.25	4.65	G8	CP3837-1004/5														
	28.0	181.0	8	S/Bobbin		195.0	160.0	5.42	D51	48	14.0	5.3	CG5	CP3580-1200/1														
	30.0	187.0	10	S/Bobbin		205.1	161.5	5.42	D46	54	20.5	3.89	CG8	CP5154-124/5														
	32.0	187.0	10						D047				CG8	CP5154-122/3														
304.0	20.7	177.8	12	Bolted	6.4	195.0	164.3	5.6	D55	48	9.0		G4 / P	CP4348-626/7														
	24.0	190.5	12	Bolted	6.4	209.3	172.0	5.6	D46	48	9.0	4.65	CG8	CP4348-938/9														
	25.4	177.8	12	S/Bobbin		195.0	152.4	4.825	D53	24	15.5	3.65	G8	Bobbin CP2494-593MB														
	25.4	177.8	12	Bolted	6.35	201.0	161.0	5.600	D52	24	15.5	3.80	G8	CP3047-404/5														
	28.0	191.0	12	Bolted	6.4	209.3	174.0	5.600	D47	48	14.0	4.90	G4	CP3580-1126/7														
	25.4	177.8	12	Bolted	6.4	203.2	164.0	4.9	D50	24	15.5			G8	CP3047-230/1													
															164.3	6.6	48	9.0	G4	CP4348-528/9								
															164.5	4.9	48	14.0	4.4	G8	CP3580-230/1							
															164.0	4.9	36	14.5	4.1	G8 / GA	CP3837-230/1							
								4.92	D47	48	14.0	4.3	GA / GA	CP3580-280/1														
	28.0	177.8	12	Bolted	6.4	201.4	161.0	6.6	D48	48	14.0	4.9		G8 / RD / T2	CP3580-66/7													
															177.8	12	Bolted	6.4	203.2	164.0	5.6	D48	24	15.5	4.5	G8	CP3047-66/7	
															177.8	12	Bolted	6.4	203.2	164.0	5.6	D48	48	14.0	5.2	G4 / GA	CP3580-2572/3	
															177.8	12	Bolted	6.4	203.2	161.0	5.6	D50	54	16.0	4.6	GA	CP5254-106/7	
															177.8	12	S/Bobbin		203.2	152.6	5.6	D50	24	15.5	4.6	G8	CP3047-270/1	
															28.0	188.0	12	Bolted	6.4	203.2	170.0	6.57	D50	48	14.0	5.2	G8	CP3580-1182/3
															28.0	190.5	12	Bolted	6.4	210.6	174.0	5.6	D47	48	14.0		G8	CP3580-1080/1
	30.0	172.0	12	Bolted	6.4	191.0	158.0	5.6	D54	54	16.0	5.6	G4	CP5254-126/7														
		32.0	177.8	12	Bolted	6.4	191.0	164.3	6.6	D54	48	14.0		G4	CP3580-2604/5													
	308.0	26.0	190.5	12						D46				CG8	CP3580-1174/5													
310.0	26.0	203.75	10	S/Bobbin		222.95	179.0	6.1	D42	48	13.5		GA	CP6565-204/5														
	28.0	190.5	12	Bolted	6.4	210.0	176.0	5.6	D50	24	15.5		G8	CP3047-212/3														
	28.0	190.5	12	Bolted	6.4	211.3	174.0	6.6	D48	48	14.0	5.2	G8	CP3580-1058/9														
	28.0	203.2	12	Bolted	6.4	220.0	190.0	5.6	D46	48	14.0	4.9	G8	CP3580-318/9														
	32.0	177.8	8	Bolted	8.2	206.9	163.1	6.3	D51	48	16.5		G8	CP3784-6080/1														
315.0	22.0	200.0	12	Bolted	6.4	220.22	180.0	5.6	D46	48	9.0		G4	CP4348-942/3														
	25.4	177.8	12	Bolted	6.4	195.0	164.5	5.3	D59	48	14.0	5.3	G4	CP3580-1012/3														
	25.4	190.5	12	Bolted	6.4	210.3	172.13	5.5	D51	48	14.0	4.77	G8	CP3580-1096/7														
	25.4	203.2	12	Bolted	6.4	220.0	190.0	5.8	D46	24	15.5	3.8	G8	CP3047-328/9														
	28.0	177.8	12	Bolted	6.4	195.1	164.3	5.8	D60	48	14.0	5.9	G4	CP3580-2416/7														
	28.0	177.8	12	Bolted	6.4	195.0	164.5	6.6	D60	48	14.0	6.2	G8	CP3580-64/5														
	28.0	177.8	12	Bolted	6.4	210.3	164.3	5.9/6.1	D52	48	14.0	5.6	CG8	Pro 5000+ & J Disc														
	28.0	190.5	12	Bolted	6.4	210.3	174.0	6.57	D51	48	14.0	5.56	G8 / GA	CP3580-1034/5														
	28.0	203.2	12	Bolted	6.4	220.0	190.0	5.6	D46	24	15.5	4.4	G8	Interchangeable	CP3047-178/9													
										48	14.0	5.4	G8	CP3580-178/9														
		32.0	177.8	12	Bolted	6.4	210.0	164.0	6.6	D51	24	15.5	6.0	G8	CP3047-216/7													
320.0	25.0	190.5	10						D50				CG8	CP3580-1110/1														
	25.4	210.5	12	Bolted	6.4	225.2	193.5	4.6	D46	24	15.5	3.6	G8	CP3047-400/1														
	28.0	191.0	12	Bolted	6.4	217.3	177.6	5.92	D50	24	15.5	4.68	CG4	CP3047-406/7														
	28.0	203.2	12	Bolted	6.4	217.3	190.0	5.57	D51	54	16.0	4.8	G8	CP5254-110/1														
	32.0	198.0	10	S/Bobbin		215.3	173.5	5.62	D51	61	20.0	5.3	CG8	Mtg flange stepped out 0.1mm														
		32.0	203.2	12	Bolted	6.4	217.3	190.0	5.57	D51	48	16.0	6.1	G8	CP3784-146/7													
322.0	30.0	203.2	12						D51				RD	CP3580-1048/9														
325.0	28.0	203.2	12	Bolted	6.4	222.0	187.0	6.6	D51	48	14.0	5.8	G4 / G8 / RD	CP3580-294/5														
328.0	28.0	203.2	12	Bolted	6.4	222.0	190.0	5.57	D52	24	15.5	5.0	G4	CP3047-144/5														
	28.0	203.2	12	Bolted	6.4	221.8	190.0	5.6	D51	24	15.5	5.2	G4	CP3047-372/3														
	32.0	217.0	8	S/Bobbin		233.1	192.0	6.3	D46	72	20.0	5.2	CG8	Bobbin CP2494-504MP														
330.0	25.4	212.0	12	Bolted	6.4	228.0	196.0	5.3	D51	48	14.0	5.2	P	CP3580-1022/3														
	25.4	214.2	12	Bolted	6.4	223.0	201.5	5.3	D46	48	14.0	4.9	G8 / GC / RD	CP3580-1040/1														
	25.4	220.5	12	Bolted	6.4	239.2	206.0	5.3	D45	48	14.0		G8	CP3580-1092/3														
	26.0	190.5	12						D53				CG8	CP3580-1230/1														
	26.0	200.0	12	Bolted	6.4	227.0	183.0	5.52	D50	48	14.0	5.2	G8	CP3580-1162/3														
	26.0	203.2	12	Bolted	6.4	225.2	184.0	5.5	D51	48	14.0	5.1	CG8	CP3580-1180/1														
	28.0	196.85	12	Bolted	6.43	217.25	215.45	7.01	D55	48	13.5	6.1	CG8	CP6565-194/5														
	28.0	203.2	12	Bolted	6.4	220.0	190.0	5.6	D54	24	15.5	5.1	G8	CP3047-252/3														
	28.0	203.2	12	S/Bobbin		227.2	178.0	6.32	D50	48	14.0	5.8	CG8	Bobbin CP2494-504MP														
	28.0	203.2	12	Bolted	6.4	227.4	185.0	5.1	D51	36	14.5	4.94	CG8	Pro 5000+ & J Disc														
	28.0	203.2	12	S/Bobbin		230.0	178.0	6.3	D50	48	14.0	5.6	G8	CP3580-2900/1														
	28.0	203.2	12	Bolted	6.4	230.0	190.0	5.6	D50	48	16.5	5.2	G8	Interchangeable, CP3580-2898/9 is a Pro 5000+ Disc														
	28.0	203.2	12	Bolted	6.4	230.0	190.0	5.6	D50	48	14.0	5.94	CG8 / G8 / RD / GA	CP3580-2898/9														
	30.0	190.5	12	Bolted	6.4	217.2	172.0	5.575	D56	48	14.0	6.8	CR8	CP3580-1130/1														
	32.0	203.2	12	Bolted	6.4	220.0	190.0	6.6	D54	48	19.5	5.8	G8	CP3581-222/3														
	32.0	203.2	12	S/Bobbin		227.0	178.0	5.6	D50	70	16.5	6.5	CG8 / GA	Bobbin CP2494-589MJ														
	32.0	203.2	12	Bolted	6.4	227.4	190.0	6.6	D51	30	15.5	6.7	CG8	Pro 5000+ Disc														
32.0	203.2	12	S/Bobbin		227.0	178.0	5.6	D51	48	19.5	5.8	CG8 / GA	Bobbin CP2494-589MJ															
32.0	203.2	12	S/Bobbin		226.0	179.0	5.6	D51	48	19.5	5.8	G8	CP3581-1130/1															
36.0	203.2	12	S/Bobbin		226.2	176.0	6.3	D50	48	19.5	6.9	G8	Bobbin CP2494-504MP															
			Bolted	6.4	219.4	190.0	6.6	D54	48	19.5	7.2	CG8	Pro 5000+ Disc															
332.0	32.0	203.2	12	Bolted	6.4	216.8	190.0	5.6	D58	48	19.5	6.2	G8	CP3581-766/7														
	26.0	210.0	12						D52				SD	CP3580-1186/7														
	31.0	210.0	10						D49				GA	CP5772-126/7														
	32.0	214.0	12	S/Bobbin		232.8	188.0	5.6	D47	48	19.5		D / GA	Bobbin CP2494-589MJ														
	32.0	214.0	12	S/Bobbin		233.1	188.0	5.6	D48	70	16.5	6.3	D / RA	CP3870-1564/5														
343.0	28.0	209.55	12	Bolted	6.43	229.5	227.7	7.01	D55	48	13.5	6.4	CG8	CP6565-192/3														
	28.0	215.9	12	Bolted	6.4	237.5	198.0	6.5	D51	48	13.5		CG8	CP6565-160/1														
	28.0	228.6	12	Bolted	6.4	240.0	212.0	5.3	D50	48	16.5	5.0	G8	CP3781-2122/3														
	28.0	228.6	12	S/Bobbin		246.0	208.0	5.4	D51	48	16.5	5.2	G8	Bobbin CP2494-591MH														