



Nominal Dimensions in (mm)																
'A' Outside Dia.	'B' Thick- ness	Mounting Details				'C' (Eye) Ø.	'D' Inside Flange Ø.	'H' Mtg. Flange	Max Pad Depth	No. of Vaness	Air Gap	Weight Kg	Face Types Available	Comments	Part Numbers	
		'M' P.C.D.	No.	Fixing Type S/Bobbin = Standard CP2494. H/Bobbin = Heavy Duty CP4135 or CP7016	Ø.											
356.0	28.0	228.6	12	Bolted	6.4	261.6	241.0	5.4	D46	48	16.5	5.5	G8		CP3781-2008/9	
	28.0	228.6	12	Floating		251.6	202.6	5.4	D51	48	16.5	5.4	CG8		CP3781-2024/5	
	28.0	228.6	12	Bolted	6.4	238.6	212.0	5.3	D54	48	16.5	5.8	CG12		CP3781-2126/7	
	28.0	240.0	12	Bolted	6.4	252.6	220.0	5.3	D51	48	16.5	5.3	CG8 / RA / RC		CP3781-2142/3	
	32.0	228.6	12	Floating		254.5	203.0	5.6	D49	36	19.5	5.7	CG8 / RA		CP3836-2048/9	
	32.0	228.6	12	Floating		244.6	202.8	5.6	D54	72	19.5	6.6	CG8 / GA / RA		CP5772-1150/1	
	32.0	228.6	12	Bolted	6.4	244.8	211.5	6.5	D54	72	17	7.4	G8		CP7177-110/1	
	32.0	228.6	12	S/Bobbin		251.6	202.6	5.6	D51	48	19.5	6.6	G8 / CG8	Bobbin CP2494-589MJ	CP3581-1080/1	
	32.0	240.0	12	S/Bobbin		258.0	215.0	5.6	D46	48	19.5			CG8	Interchangeable, Bobbin CP2494-589MJ	CP3581-1128/9
						258.6		72	19.5	5.94	CG8 / GA		CP5772-1128/9			
	32.0	240.0	12	S/Bobbin		261.6	215.0	5.6	D46	48	19.5	5.8	G8	Interchangeable, Bobbin CP2494-589MJ	CP3581-1042/3	
								36		5.3	GA / CG8 / D		CP3836-2000/1			
	32.0	240.0	12	Bolted	6.4	261.6	222.5	5.6	D46	48	19.5	5.7	G8 / P		CP3581-1038/9	
	32.0	228.6	12	Bolted	6.4	251.0	214.0	5.3	D51	48	19.5			CG8	Pro 5000+ & J Disc	CP5000-218/9
	32.0	228.6	12	Bolted	6.4	245.0	214.0	5.6	D54	48	19.5	6.7		G8 / CG24 / P		CP3581-536/7
	36.0	228.6	12	Bolted	6.4	244.6	214.0	6.6	D54	48	19.5	7.7		CG8	Pro 5000+ Disc	CP5000-110/1
	36.0	228.6	12	Bolted	6.4	245.0	208.0	6.4	D54	48	19.5	8.3		G8 / T2		CP3581-1096/7
	36.0	228.6	12	Bolted		245.0	214.0	6.6	D54	48	19.5	8.2		G8	Interchangeable	CP3581-516/7
												16.5	9.4	G8		CP3781-516/7
36.0	228.6	12	S/Bobbin		244.6	202.8	5.6	D54	48	19.5	7.6		G8	Interchangeable, Bobbin CP2494-589MJ	CP3581-1136/7	
36.0	228.6	12	S/Bobbin		251.6	202.6	6.3	D51	48	19.5	8.0		G8	Bobbin CP2494-504MP	CP3581-1078/9	
362.0	32.0	215.9	12	Bolted	6.43	238.0	195.0	6.42	D61	48	17.5	8.4	G8 / CG12 / SD		CP4542-142/3	
	32.0	215.9	12	Bolted	6.4	251.0	195.0	6.43	D54	48	17.5	7.3	CG12 / SD		CP4542-112/3	
	32.0	228.6	12	Bolted	6.4	247.2	208.0	5.95	D55	72	19.5	6.99	GA		CP5772-168/9	
	32.0	228.6	12	Bolted	6.4	251.4	208.0	6.5	D54	48	17.5	7.8	G8		CP3718-1068/9	
	32.0	228.6	12						D54					CG12		CP4542-134/5
	35.56	198.0	12						D70					CG8		CP3784-172/3
36.0	228.6	12						D					CG8		CP5772-3746/7	
366.0	32.0	240.0	12	Bolted	6.4	268.0	224.0	6.4	D48	48	17.5	6.5	G8 / GA		CP3718-1088/9	
	40.0	255.0	12	W Bobbin		270.2	230.5	5.4/5.45	D46	72	25.5	7.25	RA	Bobbin CP4015-128MD	CP6072-104/5	
370.0	36.0	209.6	12						D470				GASTL		CP3784-190/1	
	36.0	241.3	12	Bolted	6.4	252.0	224.0	6.6	D54	72	19.5	8.56	RA / P		CP5772-6072/3	
	36.0	209.6	12	Bolted	9.05	227.0	188.0	7.03	D70	48	16.0	11.5	GA		CP3784-488/9	
375.0	35.0	245.0	10	BREMBO MTG.		261.0	221.0	8.0	D54	72	19.5	8.52	P / RA	Mtg flange stepped out 1.0mm	CP5772-104/5	
	36.0	247.6	12	Bolted	6.4	257.0	231.0	6.6	D54	72	19.5	8.63	P / RA		CP5772-1076/7	
	36.0	241.3	12	Bolted	6.4	257.0	225.0	6.6	D54	72	19.5	8.72	CG8 / P / RA		CP5772-6076/7	
376.0	28.0	260.0	12	S/Bobbin		277.6	235.4	5.6	D47	48	17.5	5.1	G8	Bobbin CP2494-589MJ	CP3718-1000/1	
378.0	28.0	260.3	12	Bolted	6.4	282.0	244.0	6.07	D46	48	13.5	6.1	G12	Mtg flange stepped out 1.0mm.	CP5914-116/7	
	32.0	235.8	10	Bolted	8.4	250.0	218.0	7.0	D64	48	16.0		CR8	Interchangeable	CP3784-2098/9	
					8.4	250.0	220.0	7.0	D64	48	17.5		G8		CP3718-2020/1	
	32.0	240.0	12	S/Bobbin	267.0	214.5	5.6	D54	36	19.5	6.6		CG8 / GA	Interchangeable, Bobbin CP2494-589MJ	CP3836-1030/1	
					268.0	215.0	5.6	D54	48	17.5	7.2		CG8 / G8	CP5772-1030/1 is a Pro 5000) Disc	CP3718-1030/1	
								72	19.5	7.16		CG8 / GA / P		CP5772-1030/1		
								72 'S'	20.0	7.46		CG8 / GA	'S' Vane Disc Bobbin CP2494-589MJ		CP6972-1030/1	
	32.0	260.4	12	Bolted	6.4	282.6	243.8	5.8	D48	36	19.5	5.8	GA / G8		CP3836-2002/3	
	32.0	260.4	12	S/Bobbin		282.7	235.0	5.625	D46	36	19.5	5.87	CG8 / GA		CP3836-1010/1	
	32.0	260.4	12	S/Bobbin	282.0	235.5	5.6	D46	72	19.5	6.2		GA	Bobbin CP2494-589MJ	CP5772-1010/1	
					235.35	5.6	D46	72 'S'	20.0	6.4	GA	'S' Vane Disc Bobbin CP2494-589MJ		CP6972-1010/1		
	34.0	224.0	10						D66				GA / G12		CP3784-1570/1	
	34.0	247.65	12						D54					CG8		CP7177-144/5
	34.0	247.6	12	W Bobbin	266.85	221.0	6.82	D54	72	19.5	7.9		GA	Bobbin CP4135-107FR	CP5772-2086/7	
					72 'S'	20.0	8.19	CG8	'S' Vane Disc / Bobbin CP4135-107FR		CP6972-206/7					
	36.0	240.0	12	S/Bobbin		264.9	216.0	5.6	D54	48	17.5	8.9	CG8 / GA	Bobbin CP2494-589MJ	CP3718-2068/9	
	36.0	240.0	12	S/Bobbin	1	264.0	214.5	5.6	D54	72	19.5	8.9	CG4 / CG8 / CG24 / RA / G8	CP5772-1032/3 is a Pro 5000) Disc	CP5772-2068/9	
	36.0	240.0	12	S/Bobbin		266.0	215.0	5.6	D54	72	19.5			G8		CP5772-1032/3
36.0	240.0	12	S/Bobbin		266.8	214.5	5.6	D54	72 'S'	20.0	8.9		RA	'S' Vane Disc Bobbin CP2494-589MJ	CP6972-2068/9	
36.0	247.6	12	H/Bobbin		266.8	221.0	7.5	D54	72	20.0	8.7		CG8 / GA	Wide Bobbin Disc CP7016-139MS	CP5772-2084/5	
37.0	275.0	12						D42					RA		CP6072-130/1	
380.0	28.0	238.0	12	Bolted	9.05	265.0	218.0	7.03	D55	48	13.5	7.6	GA		CP5914-484/5	
	28.0	240.0	12		9.13/8.98	265.0		7.08/6.93	D54	48	13.5		CG12		CP5914-184/5	
	32.0	228.6	10	S/Bobbin		247.0	202.2	5.6	D66	72	19.5	8.4	CG8	Bobbin CP2494-589MJ	CP5772-118/9	
	34.0	250.5	12						D54					GA		CP4284-580/1
	36.0	214.2	12	Bolted	9.05	236.0	195.5	7.03	D70	72	17.0	11.6		GA		CP7177-448/9
	37.0	240.0	12	Floating		270.0	215.0	5.4	D54	72	25.5	7.68		CG24 / GA		CP6072-108/9
40.0	240.0	12	S/Bobbin		266.0	216.0	5.4	D54	72	25.5	8.8		CR24 / RA		CP6072-102/3	
400.0	32.0	223.0	12						D70					CG12		CP7177-130/1
	32.0	260.0	12		6.4	268.8	243.0	6.3	D54	54	19.0	7.68		CG24		CP4095-110/1
	34.0	260.0	12	Bolted	6.4	278.8	243.0	6.14	D54	84	21.0	8.0		CG24		CP4284-112/3
	36.0	223.0	12	Bolted	8.1	247.0	202.0	7.00	D70	72	17.0	11.95		GA		CP7177-124/5
	36.0	228.6	12	Bolted	9.05	247.0	208.0	7.03	D70	72	17.0	11.90		GA		CP7177-406/7
	36.0	240.0	12	W Bobbin		258.9	215.0	6.8	D62	84	21.0	10.0		CG8	Bobbin CP4135-107FR	CP4284-136/7
	36.0	260.0	12	Bolted	6.4	268.8	243.0	6.3	D54	54	19.0	9.3		CG24		CP4095-100/1
36.0	260.0	12	Floating		278.75	235.0	6.8	D54	84	21.0	8.7		CG8 / GA	Pro 5000) Disc Bobbin CP4135-107FR	CP4284-134/5	
410.0	36.0	245.5	12	Bolted	8.25	266.00	225.5	8.10	D70	73	19.0			GC8 / G8		CP4095-102