

TECHNICAL DATA SHEET



Product Code: 8123 Sector: Automotive

Issue No: 1

Issue Date: 23/07/20

TRIDENT PROFESSIONAL ENGINE OIL C2/C3 5w30

Fully synthetic, mid SAPS, for use in petrol, diesel and hybrid engines.

Application

A professional engine oil suitable for the latest engine technology. Designed to meet OEM specifications. Recommended for engines requiring a C2 or C3 5w30 viscosity meeting the below manufacturer specifications.

Performance Profile

ACEA C2/C3

API SN, CF

Suitable for

BMW Longlife-04

Fiat 9.55535-S3, Fiat 9.55535-S1

GM dexos 2

GM-LL-B-025, GM-LL-A-025

MB 229.52, MB 229.51, MB 229.31

PSA B71-2290 <2014

Renault RN0700

VW 502 00 / 505 01, VW 502 00 / 505 00

Asian manufacturers

Features & Benefits

- Excellent low temperature flow when cold starting, helping to instantly protect vital components.
- Viscosity stability at high temperatures, delivering reduced wear and tear on the engine and its components.
- Formulated with technology to provide engine cleanliness and durability which improves fuel economy, reduces emissions and provides extended drain capability.
- Utilising mid SAPS technology protecting particulate filters and controlling soot build up.
- Millers Oils stop start technology delivers instant protection under hot or cold conditions.

Typical Characteristics

Density @ 15°C, g/ml	0.848
Kinematic Viscosity @ 100°C, cSt.	11.8
Flashpoint, °C	>200

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, OEM – Original Equipment Manufacturer



MADE IN BRITAIN

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.co.uk