

TECHNICAL DATA SHEET



Product code: 7640 **Sector:** Automotive

Issue No: 1

Issue Date: 11/08/20

XF PREMIUM ENGINE OIL C3 5w40

Fully synthetic, mid SAPS, for use in petrol, diesel and hybrid engines.

Application

A premium OEM approved engine oil formulated using the latest technology for applications requiring a C3 5w40 viscosity. Targeting 'Pumpe Düse' PD Volkswagen Audi Group (VAG) engines including Lamborghini, Seat, Skoda and Porsche. Other coverage includes GM and Mercedes Benz.

Performance Profile

ACEA C3
API SN
BMW Longlife-04
GM dexos 2
MB 229.52, MB 229.51
Porsche C40 (Approved)
Renault RN0700 / RN0710
VW 511 00

Suitable for

API CF
Chrysler MS-11106
Fiat 9.55535-GH2, Fiat 9.55535-T2, Fiat 9.55535-S2
Ford WSS-M2C917-A
GM-LL-B-025, GM-LL-A-025
MB 229.31, MB 226.5
Opel/Vauxhall OV0401547
Porsche A40
VW 502 00 / 505 01, VW 502 00 / 505 00
VW 500 00 / 501 01
Lamborghini
Asian manufacturers

Typical Characteristics

Density @ 15°C, g/ml	0.847
Kinematic Viscosity @ 100°C, cSt.	13.3
Flashpoint, °C	>200

Features & Benefits

- XF Premium engine oil with Millers Oils Dynamic Fluid Technology (DFT) provides enhanced low temperature flow when cold starting, instantly protecting the vital components of the engine from the very start of every journey.
- XF Premium engine oil with DFT maximises viscosity stability at high temperatures. This reduces engine wear giving superior protection for components including pistons, rings, timing chain, bearings and valve lifters.
- DFT specifically engineered to enhance engine cleanliness, delivering improved fuel economy, reduced emissions and extended service drain capability.
- DFT delivers outstanding instant protection under hot and cold temperatures, whilst simultaneously reducing fuel consumption and lowering exhaust emissions.
- XF Premium engine oil with DFT is specifically formulated for use in all hybrid systems including self-charging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHEV).
- Compatible for use with bio fuels, DFT provides exceptional performance and protection against deposits, sludge and engine wear.

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, DFT – Dynamic Fluid Technology, OEM - Original Equipment Manufacturer.
Asian manufacturers – Including but not limited to Honda, Hyundai, Infiniti, Kia, Lexus, Nissan, Suzuki and Toyota.



MADE IN BRITAIN

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.co.uk