

TECHNICAL DATA SHEET



Product code: 8175 **Sector:** Automotive

Issue No: 1

Issue Date: 11/08/20

XF PREMIUM ENGINE OIL C5 0w20

Fully synthetic, mid SAPS, for use in petrol, diesel and hybrid engines.

Application

A premium OEM approved engine oil formulated using the latest technology for applications requiring a C5 0w20 viscosity, covering a wide range of European and Asian manufacturers.

Performance Profile

ACEA C5

API SN PLUS RC, SN PLUS, SN

BMW Longlife-17 FE+ (Approved)

ILSAC GF-5

MB 229.71

Opel/Vauxhall 0V0401547 * (Approved)

*suitable for use in GM dexos 2 and dexos D applications.

Suitable for

API SM

BMW Longlife-14 FE+

Chrysler MS-12145

Fiat 9.55535-GSX, Fiat 9.55535-DSX

Ford WSS-M2C947-B1, Ford WSS-M2C952-A1

Jaguar Land Rover STJLR.51.5122, Jaguar Land

Rover STJLR.03.5006

Volvo VCC RBS0-2AE

Asian manufacturers

Typical Characteristics

Density @ 15°C, g/ml 0.845

Kinematic Viscosity @ 100°C, cSt. 7.8

Flashpoint, °C >200

Features & Benefits

- XF Premium engine oil with Millers Oils Dynamic Fluid Technology (DFT) provides enhanced low temperature flow when cold starting, instantly protecting the vital components of the engine from the very start of every journey.
- DFT specifically engineered to enhance engine cleanliness, delivering improved fuel economy, reduced emissions and extended service drain capability.
- DFT complements and utilises latest mid SAPS technology protecting after treatment systems such as particulate filters, Selective Catalytic Reduction (SCR) and AdBlue delivering our ultimate soot control and environmental protection.
- DFT delivers outstanding instant protection under hot and cold temperatures, whilst simultaneously reducing fuel consumption and lowering exhaust emissions.
- XF Premium engine oil with DFT delivers outstanding LSPI (Low Speed Pre-Ignition) protection and our ultimate in turbo charger care, even under the most extreme operating conditions.
- XF Premium engine oil with DFT is specifically formulated for use in all hybrid systems including self-charging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHEV).

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website

www.millersoils.co.uk

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, DFT – Dynamic Fluid Technology, OEM – Original Equipment Manufacturer.

Asian manufacturers – Including but not limited to Honda, Hyundai, Infiniti, Kia, Lexus, Nissan, Suzuki and Toyota.



MADE IN BRITAIN

Millers Oils Ltd

Brighouse West Yorkshire HD6 3DP UK

Tel: +44(0) 1484 713201

www.millersoils.co.uk