

## ATF Additive

### Description

The additives contained provide optimal care of rubber and plastic seals in the steering gear and automatic transmission. Leaks on transmissions caused by hardened or brittle seals are prevented or remedied. Holes and ducts in the gears are also cleaned, and the performance of the oil is revitalized. The noise generation of power steering systems is reduced and the shifting operations of automatic transmissions are improved. Can extend the service life of steering gears and automatic transmissions and lower the repair costs.

### Properties

- regenerates seals
- prevents oil loss
- care and protection
- cleans and maintains
- stable to oxidation
- minimizes unwanted noise
- prevents expensive repairs
- increases service life
- high wear resistance
- prevents rapid aging of oil
- damps shifting operations

### Technical data

Color / appearance	brown
Viscosity at 40 °C	~ 166 mm <sup>2</sup> /s DIN 51562
Viscosity at 100 °C	~ 26 mm <sup>2</sup> /s DIN 51562
Density	0,888 g/ml
Refractive index at 20 °C	~ 1,478
Form	liquid
Odor	characteristic

### Areas of application

Suitable for all steering gears and automatic transmissions that are filled with ATF II and ATF III oils.

### Application

Mix additive into the gear oil using the dipstick. Contents (250 ml) sufficient to treat up to 8 liters of oil.

### Available pack sizes

250 ml Tube plastic	2702 GB-AUS
250 ml Tube plastic	5135 D-GB-I-E-P



### Available pack sizes

250 ml Tube plastic	8336 GB-ARAB-F
---------------------	-------------------

**Our information is based on thorough research and may be considered reliable, although not legally binding.**