



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES: CVL TURBO

Product No	5792
Issue No.	2
Issue Date	17/01/17

DESCRIPTION:

Octane booster, valve seat lubricant and combustion enhancer.

APPLICATION:

One bottle [500 mls] to 20 litres [maximum] unleaded petrol for all motorsport applications. Precise treatment levels should be determined by test bed experimentation.

Storage Instructions: Avoid strong direct light and heat

USER BENEFITS:

- Use with modern fuels to increase octane levels by up to 4 octane numbers (40 points).
- Provides improved performance for race, rally or track day.
- Provides similar flame front control as lead, thereby enabling engines to run more advanced ignition timing without danger of pre-ignition or detonation.
- Mixes with leaded, unleaded, LRP and other fuels containing octane enhancing additives such as oxygenates, ethanol and MTBE.
- Equally effective in modern engines fitted with knock sensors and catalytic convertors.

PERFORMANCE PROFILE:

- For maximum benefit use in conjunction with premium, higher octane unleaded fuel.
- Used by an increasing number of engine builders to compensate for the deterioration in pump fuel.

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C 0.910
Flashpoint °C >62

Colour Pale Yellow Liquid

HEALTH AND SAFETY:

Health and Safety Data Sheet 5792 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk