



Gear Oil 4005 LS 75w140

DESCRIPTION

Gear Oil 4005 LS 75W-140 is a synthetic lubricant for gears, especially developed for lubricating differentials, gear boxes and axles of sports cars and commercial vehicles used in severe applications.

Excellent Performances – Total Protection

Its extraordinary E.P. and AW properties (“Extreme Pressure” and “Anti-wear”), its special “Limited Slip” additive and its strong resistance to deterioration by use make it very suitable to be employed with traditional hypoid differentials and self-blocking differentials that undergo a strong stress and with gear systems exposed to high temperatures for a long time.

Very well indicated for BMW differentials, for which “Limited Slip” lubricants are required.

SPECIFICATIONS

API GL-5 / MT-1 / MACK GO-J / SAE J2360

PROPERTIES

- Best protection of gears against wear, strong loads and rust.
- Better transmission efficiency, better fuel economy.
- Assures longer life and cleanliness to all transmission parts.
- Good resistance against deterioration and thermal oxidation.
- Inhibits the formation of foam.
- 100% synthetic formula.

TECHNICAL DATA

Viscosity at 40°C	126 ,3
Viscosity at 100°C	25,3
Viscosity at 15°C	0,867
Viscosity Index	236
Flash point	131
Pour Point	-39

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.





TECHNICAL DATA SHEET V042021

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

426039	12 x 1L
--------	---------



BARDAHL | *NOTHING WILL STOP YOU*

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2
T: (+32) (0) 69 59 03 60

www.bardahl.fr
www.bardahloils.com