



Gear Oil 4005

DESCRIPTION

Gear Oil 4005 is a Total Driveline fully synthetic oil, developed for lubricating the manual transmissions and the differential units of standard vehicles, sports cars and commercial vehicles.

Its extraordinary E.P. (Extreme Pressure) properties and its excellent resistance to degradation from use make it suitable for strongly stressed hypoid differentials and for gear systems exposed to high temperatures for a long time.

SPECIFICATIONS

API GL-4, API GL-5 / MT-1 / SAE J2360 / MIL-PRF-2105E / MAN M 3343 Type S, M341 Type E-3 / DAF / IVECO / SCANIA STO 1:0 / MB 235.8 / ARVIN MERITOR / MACK GO-J / ZF TE ML 02B, 05B, 07A, 08, 12B, 16F, 17B, 19C, 21B.

PROPERTIES

- Best protection of gears against wear and heavy loads.
- Improved effectiveness of transmission.
- Guaranteed longer life and better cleanliness of all parts of transmission.
- Excellent resistance against deterioration and thermal oxidation.
- Compatibility with synchronizers and elastomers.
- Helps to extend the oil change interval as indicated by manufacturer.

TECHNICAL DATA

Viscosity at 40°C	107,9
Viscosity at 100°C	15,8
Viscosity at 15°C	0,869
Viscosity Index	157
Flash point	146
Pour Point	< -36°C

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.





TECHNICAL DATA SHEET V042021

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

430039	12 x 1L
--------	---------



BARDAHL | *NOTHING WILL STOP YOU*

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2
T: (+32) (0) 69 59 03 60

www.bardahl.fr
www.bardahloils.com