

Product code: 8376 Sector: Automotive

Issue No: 1

Issue Date: 06/05/22

## XF Premium MTF 75w90

Fully synthetic gear oil for use in gearboxes, transfer cases & differentials.

### Application

A premium OEM gear oil formulated using the latest technology for gearbox applications requiring a 75w90 viscosity. Predominantly for European and Asian manufacturers.

### Suitable for

API GL-4, GL-5

BMW MTF LT-4

Fiat 9.55550-MX3

Ford M2C203-A1, M2C200-C3, M2C200-C,

M2C200-B, M2C180-A, M2C175-A

GM/Opel/Saturn 1940768, 1940182, 1940004

PSA 9730 A2

Volvo 1161723, 97309

VW/Audi/Seat/Skoda TL 529 11 (P/N G 052 911),

TL 521 45 (P/N G 052 145),

TL 501 50 (P/N G 050 150)

Abarth, Acura, Alfa Romeo, Aston Martin, Austin, BMW, Brabus, Bugatti, Chery, Chevrolet, Chrysler, Dacia, Daihatsu, Dodge, Ferrari, Fiat, Ford, GMC, Honda, Hyundai, Infiniti, Isuzu, Jaguar, Jeep, Kia, Lada, Lancia, Land Rover, Lexus, Lotus, Maserati, Mazda, Mercedes-Benz, MG, Mini, Mitsubishi, Morgan, Nissan, Opel, Pontiac, Proton, PSA Inc. Peugeot, Citroen, DS, Rover, Saab, Smart, SsangYong, Subaru, Suzuki, The London Taxi Company, Toyota, TVR, Vauxhall, Volvo, VWAG Inc. VW, Audi, Seat, Skoda, Porsche, Bentley, Lamborghini

### Features & Benefits

- XF Premium gear oil provides enhanced low temperature flow when cold starting, instantly protecting the vital components of the gearbox from the very start of every journey.
- XF Premium gearbox oil maximises viscosity stability at high temperatures. This reduces gearbox wear giving superior component protection including gear teeth, shafts and bearings.
- Delivers outstanding lubrication and instant protection under hot and cold temperatures.
- XF Premium gear oil is specifically formulated for use in hybrid systems including self-charging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHEV).

### Typical Characteristics

Density @ 15°C, g/ml	0.865
Kinematic Viscosity @ 100°C, cSt	14.0
Flash Point, °C	>220

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website

[www.millersoils.co.uk](http://www.millersoils.co.uk)

Footnotes: P/N – OEM Part Number



MADE IN BRITAIN 

Millers Oils Ltd  
Brighouse West Yorkshire HD6 3DP UK  
Tel: +44(0) 1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)